


**NEW** 裸圧着端子 角先開形 (A形)  
新製品



仕様

●材質:無酸素銅

UL LISTED E42024 SP LR20812

商品コード	品番	規格	寸法 (mm)								適用電線範囲	標準単価	梱包	出荷単位
			d <sub>2</sub>	B	L	F	E	øD	ød <sub>1</sub>	T				
690-350-00830	1.25-C3A JP		3.2	5.6	15.8	6.3	4.8	3.4	1.7	0.8	単線:0.57~1.44mm より線:0.25~1.65mm <sup>2</sup> AWG:#22~#16	1,000個 (10箱)	100個 (1箱)	
690-350-00840	1.25-B3A JP			5.8										
690-350-00850	1.25-M3A JP			6.35										
690-350-00860	1.25-C3.5A JP		3.7	5.6	15.8	6.3								
690-350-00870	1.25-N3A JP			6.2										
690-350-00880	1.25-YS3A JP		4.3	6.4	15.4	6.3								
690-350-00890	1.25-YS4A JP			6.4										
690-350-00900	1.25-S4A JP			7.2										
690-350-00910	1.25-4A JP		5.3	8.5	15.8	7.0								
690-350-00920	1.25-5A JP			9.5										
690-350-00930	1.25-6A JP		6.4	12.0	22.0	11.0								
690-350-00940	2-N3A JP		3.2	5.9	15.8	6.3	4.8	4.1	2.3	0.8	単線:1.14~1.82mm より線:1.04~2.63mm <sup>2</sup> AWG:#16~#14	オープン	1,000個 (10箱)	100個 (1箱)
690-350-00950	2-C3.5A JP			5.6										
690-350-00960	2-YS3A JP			3.7	6.4									
690-350-00970	2-S3A JP		4.3	7.2	16.0	6.5								
690-350-00980	2-YS4A JP			6.4										
690-350-00990	2-S4A JP		5.3	7.2	16.0	6.5								
690-350-01000	2-4A JP			8.5										
690-350-01010	2-5A JP		6.4	9.5	16.8	7.3								
690-350-01020	2-6A JP			12.0										
690-350-01030	5.5-S3A JP		3.7	7.2	19.5	7.5								
690-350-01040	5.5-3A JP			9.5										
690-350-01050	5.5-S4A JP		4.3	8.5	19.5	7.5								
690-350-01060	5.5-4A JP			9.5										
690-350-01070	5.5-5A JP		6.4	9.5	25.5	12.2								
690-350-01080	5.5-6A JP			13.5										
690-350-01090	5.5-8A JP		8.4	13.5	25.5	12.2								